

### **1 Each – 3,000LB Walker Reach Stacker**

24V infinitely variable transistor travel control •AC drive motor •Power steering with side shift •PDSR battery compartment: 31.6" x 9.06" x open •PDSR30-157 battery compartment: 31.6" x 13" x open •Connector: SB-175 Red •Drive Tire: (1) 10" x 4" Polyurethane •Load Wheels: (2) 4" x 2.75" Polyurethane •Offset control handle, thumb control travel functions •Proportional lift, lower, tilt extend and side shift controls in handle •Ergonomic control head with belly button reversing switch •Standard fork size: 42" x 4" x 1.5" •PDSR30-189 straddle ID/OD: 42/50 only •Tilting fork carriage: 2° forward / 4° backward •Built-in pressure relief valve •Dual lifting chains •30.8" wide carriage with 36" tall load backrest •Fixed straddle legs •Battery discharge indicator hour meter, horn and key switch • Polycarbonate mast guard Mast 3- Stage Lift Height 189" Collapsed height 88.3" Free lift 41 Extended height 227 Weight<sup>2</sup> 4200 Lithium battery pack UL recognized, 205Ah LFP battery with integral 30A, 120VAC charger. Only available for PDSR30-106, PDSR30-126 and PDSR30-157

### **1 Each - Walker Reach Stacker Charging Station**

### **4 Each – 4,000 LB Electric Pallet Jack**

4,000 LB. Capacity Lithium-Ion Pallet Jack-Class 3 • 48V Curtis travel control • Permanent magnet DC drive motor •Easy Exchange lithium-ion battery system (1) 48V 30Ah rechargeable battery 15A, 120VAC plug-in smart charger •Drive Tire: (1) 8.3" x 2.8" Polyurethane •Load Wheels: (2) 2.9" x 3.5" Polyurethane •Powered lift and lower control •Powered travel - forward and reverse •Dual butterfly infinitely variable travel controls •Travel speed: 3.1 mph loaded, 3.4 mph unloaded •Ergonomic control head includes key switch, creep speed travel control, battery discharge indicator, battery wake-up, belly button reversing switch and horn •Medium gauge tapered and shaped forks •Fork raised height: 7.75" •Fork lowered height: 3.2" •Fork width: 6" •Estimated duty cycle: 3 hours, continuous •Estimated charging time: 1.5 hours Forks 27 x 48 Fork Width 27" Fork length 46" OAW 27.4" OAL 63" Weight<sup>2</sup> 390

### **1 Each – 5,500 LB Fork Lift**

5,500 Lb Capacity LP Fork Lift Free Lift Triplex Mast FLT Height 4800 mm 15'-9" Mast Tilting forward backwards 66 Side shift carriage cascade width 1038 mm 3'-5" Load Backrest width 1038 mm 3'-5" Distributor 3 HYD Movement with Mechanical level controls HYD Kit 3rd Element Tires Front and Rear Advance 7.0012 12 6.009 10 Solid Mechanical Suspension Vinyl Seat Grammer MSG 65 Halogen Rear Work light LED Amber Strobe Light Halogen Front Work Lights x2 Halogen Rear Road Lights Duel Fuel LPG/Gasoline Exhaust in counterweight Operator Presence System OPS USA & Canada Machine Homologation STD

Carriage Affaire Speciale Predisposition Easy Link Fork 122x 40x 1220 mm 4.8 x 1.5x 48 IN  
Parts Catalog Maintenance Booklets Operators Manuel

**1 Each – Scissor Lift 32”**

Scissor Lift 32’ Platform Height x 47” Width Roll-out-deck extension w/ dual locks • Non-marking tires • Swing-out service trays • Saloon-door-style entry gates • Operates at full height indoor & outdoor • Descent & All-motion alarms • Proportional controls, including descent • Loading pendant • Power line to platform • Platform overload system • Hour meter & on-board diagnostics display • Integrated battery charger • Battery condition indicator • Flashing amber strobe • Crane & forklift pockets • Lanyard attachment points • Scissor stack roller slide plates (set of 2)

**1 Each – Scissor Lift 19”**

Scissor Lift 19’ Platform Height x 32” Width, Fully electric drive • Fully electric steer • No hydraulic hoses • Roll-out deck extension w/ dual locks • Non-marking tires • Spill containment tray • Swing-out service trays • Single-gate entry • Operates at full height indoor & outdoor • Descent and all-motion alarms • Flashing amber strobe • Proportional control, including descent • Platform overload system • Power to platform • On-board diagnostics, hour meter, battery meter • Integrated battery charger • Crane & forklift pockets • Lanyard attachment points • 2,000 charging cycles / 5-year\*\* lithium battery warranty

**2 Each – Manual Pallet Jacks**

Standard size 48x27 Load Capacity 5,500 lbs

**2 Each – U-boats**

24x60 Green Load Capacity 1,800 lbs no top shelf

**1 Each - Forklift Carpet Pole**

120” Mass Mount Load Capacity 2,200

**1 Each - Carpet Dolly**

8 Ft – 20x96x21

**2 Each – Steel Hand Trucks**

Loop Handle with XL Nose Plate 20x22x51 estimated size

**2 Each - Platform Carts**

24x48 Plastic Capacity Load 2,000 lbs